
S 89°42'25" W 2523.12' SEC 24 SEC 19 DESCRIPTION OF SITE 1 N 88°11'54" E 1853.17 89'36'51" S 89°45'38'' 1851.83 5/8"X24" REBAR WITH CAPS STAMPED 148951 SET AT SITE CORNERS DESCRIPTION OF SITE 2 RADIUS:300' SITE 1 NARRATIVE C175 0 C100 / • LAT: 40°06'07.124" LONG: 110°02'57.861" KNOWLEDGE. N 89°57'54" E SEC 24 SEC 19 SEC 25 <sup>↑</sup> SEC 30

PROPERTY & TOPOGRAPHIC SURVEY FOR

## TENNESSEE VALLEY AUTHORITY

SECTION 19, TOWNSHIP 8 SOUTH, RANGE 17 EAST

SALT LAKE BASE AND MERIDIAN



Beginning at a point on the South right—of—way line of a County Road, said point being South 89°45'38" East 1851.83 feet from the West Quarter Corner of Section 19, Township 8 South, Range 17 East of the Salt Lake Base and Meridian; Thence South 89°36'51" East 1000.00 feet along said south Right—of—way line; Thence South 0°23'09" West 1000.00 feet; Thence North 89°36'51" West 1000.00 feet; Thence North 0°23'09" East 1000.00 feet to the Point of Beginning, containing 22.96 acres, with a bearing of North 0°02'00" East from the Southwest Corner of said Section 19 to said West Quarter Corner being used as the basis of bearings. West Quarter Corner being used as the basis of bearings.

Beginning at a point on the North right—of—way line of a County Road, said point being North 88°11'54" East 1853.17 feet from the West Quarter Corner of Section 19, Township 8 South, Range 17 East of the Salt Lake Base and Meridian; Thence North 0°23'09" East 1000.00 feet; Thence South 89°36'51" East 1000.00 feet; Thence South 0°23'09" West 1000.00 feet; Thence South 0°23'09" West 1000.00 feet;

Thence North 89°36'51" West 1000.00 feet along said North right—of—way line to the Point of Beginning, containing 22.96 acres, with a bearing of North 0°02'00" East from the Southwest Corner of said Section 19 to said West Quarter Corner being used as the basis of

This survey was performed at the request of Tennessee Valley Authority to locate the corners and map two possible G.P.S. tower sites. The General Land Office Corners indicated on the plat were found and used to control the survey. The latitudes and longitudes were determined by using a Timble Pro XRS receiver with an Omnistar Satellite link. The values yielded by this system are sub-meter positions. The survey was performed using a combination of G.P.S. equipment and procedures and conventional survey techniques.

SURVEYOR'S CERTIFICATE

THIS IS TO CERTIFY THAT I HAVE SURVEYED THE PARCELS SHOWN ON THIS PLAT, AND THAT THE MONUMENTS INDICATED WERE FOUND OR SET DURING SAID SURVEY, AND THAT THIS PLAT ACCURATELY REPRESENTS SAID SURVEY TO THE BEST OF MY



SEC 19 SEC 20 SEC 30 \$\infty\$ SEC 29

JERRY D. ALLRED, REGISTERED PROFESSIONAL LAND SURVEYOR, CERTIFICATE NO. 148951

COUNTY SURVEYOR'S FILE # 970 JERRY D. ALLRED & ASSOCIATES SURVEYING CONSULTANTS 121 NORTH CENTER ST.—P.O. BOX 975 DUCHESNE, UTAH 84021 (435) 738—5357

00-100-B23